

## SAFETY DATA SHEET

Issue Date 13-Dec-2012

Revision Date 01-Oct-2017

Version 1

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier** 

**Product Name** 

Silicone Sealant - Acetoxy Cure - Clear, White & Colors

Other Means of Identification

SDS#

RD-0081

**Product Code** 

0810, 0816, 0826 Series

Recommended Use of the Chemical and Restrictions on Use

Recommended Use

Silicone Sealant.

Details of the Supplier of the Safety Data Sheet

Supplier Address Red Devil, Inc. 4175 Webb Street Pryor, Oklahoma 74361 www.reddevil.com

**Emergency Telephone Number** 

Company Phone Number

918-825-5744 Fax: 918-825-5761

**Emergency Telephone** 

INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

## 2. HAZARDS IDENTIFICATION

## Classification

Skin corrosion/irritation

Category 2

Signal Word Warning

**Hazard Statements** 

Causes skin irritation



Appearance Clear/opaque or colored paste

Physical State Paste

Odor Acetic Acid Odor (Vinegar odor)

#### Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection

### Precautionary Statements - Response

IF ON SKIN: Wash with plenty of soap and water If skin irritation persist: Get medical advice/attention Take off contaminated clothing and wash before reuse

#### Hazards Not Otherwise Classified (HNOC)

Not Applicable

#### Other Information

Not Applicable

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Hydroxy-terminated Dimethyl siloxane	70131-67-8	>50
Non-hazardous ingredients *	Proprietary	>10
Amorphous silica (glass)	7631-86-9	<13
Polydimethylsiloxane	63148-62-9	<10
Methyltriacetoxysilane	4253-34-3	<6
Titanium Dioxide	13463-67-7	<5
Ethyltriacetoxysilane	17689-77-9	<6

<sup>\*</sup> Unlisted ingredients are not considered hazardous under the OSHA GHS Hazard Communication Standard (29 CFR 1910.1200). (Methyltriacetoxysilane) Observe limits for acetic acid formed during curing on exposure to water or humid air. (Silica, amorphous; Titanium Dioxide) Inhalation of particulates unlikely due to product's physical state

## 4. FIRST AID MEASURES

### First Aid Measures

General advice Provide this SDS to medical personnel for treatment.

Inhalation If symptoms are experienced remove source of contamination or move victim to fresh air. If

irritation persists, obtain medical advice.

Eye Contact Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 5

minutes while holding the eyelid(s) open. Obtain medical attention.

Ingestion Rinse mouth thoroughly with water. If irritation or discomfort occurs, obtain medical advice.

Skin Contact No health effects expected. If irritation does occur, flush with lukewarm, gently flowing water

for 5 minutes. If irritation persists, obtain medical advise.

## Most Important Symptoms and Effects, both Acute and Delayed

Symptoms Causes skin irritation. May cause nose, throat & respiratory tract irritation. Direct contact

with eyes may cause temporary irritation.

## Indication of any Immediate Medical Attention and Special Treatment Needed

Note to Physicians

Treat according to person's condition & specifics of exposure.

## 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Small Fire

Use carbon dioxide (CO2), dry chemical or water spray.

Large Fire

Use dry chemical, foam or water spray.

Unsuitable Extinguishing Media Not determined.

## Specific Hazards Arising from the Chemical

Not determined.

Hazardous combustion products Carbon oxides & traces of incompletely burned carbon compounds. Silicon dioxide. Formaldehyde.

Protective Equipment and Precautions for Firefighters

Self-contained breathing apparatus & protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

## 6. ACCIDENTAL RELEASE MEASURES

## Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions

Observe all personal protection equipment recommendations described in Sections 5 & 8.

**Environmental Precautions** 

See Section 12 for additional ecological information.

## Methods and Material for Containment and Cleaning Up

Methods for Containment

Prevent further leakage or spillage if safe to do so. Use absorbent material to contain spill.

Methods for Cleaning Up

Wipe up or scrape up & contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Local, state & federal laws & regulations may apply to releases & disposal of this material as well as those materials & items employed in the cleanup of releases. You will need to determine which federal, state & local laws & regulations are applicable. Sections 13 & 15 of this MSDS provide information regarding certain federal & state requirements.

## 7. HANDLING AND STORAGE

#### **Precautions for Safe Handling**

Advice on Safe Handling

Handle in accordance with good industrial hygiene and safety practice. Wash face, hands, and any exposed skin thoroughly after handling. Use personal protection recommended in Section 8. Use only in well-ventilated areas. Avoid contact with skin and eyes. Product evolves acetic acid (HOAc) when exposed to water or humid air.

## Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions Keep container closed & store away from water or moisture.

Incompatible Materials Oxidizing material can cause a reaction. Water, moisture or humid air can cause hazardous

vapors to form as described in Section 8.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Guidelines**

Exposure guidelines / protective equipment are for routine handling and accidental spills

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Amorphous silica (glass) 7631-86-9	-	(vacated) TWA: 6 mg/m³ <1% Crystalline silica TWA: 20 mppcf : (80)/(% SiO2) mg/m³ TWA	IDLH: 3000 mg/m³ TWA: 6 mg/m³
Titanium Dioxide 13463-67-7	TWA: 10 mg/m³	TWA: 15 mg/m³ total dust (vacated) TWA: 10 mg/m³ total dust	IDLH: 5000 mg/m³

Other Information

Acetic acid is formed upon contact w/ water or humid air. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA 10 ppm & ACGIH TLV: TWA 10 ppm, STEL 15 ppm.

#### Appropriate Engineering Controls

**Engineering Controls** 

Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS. Good general ventilation should be sufficient.

## Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection

Safety glasses as a minimum for protection.

Skin and Body Protection

Wear suitable protective clothing.

Respiratory Protection

No special equipment needed.

General Hygiene Considerations

Note: These precautions are for room temperature handling. Use @ elevated temperature or aerosol/spray applications may require added precautions. Handle in accordance with good industrial hygiene and safety practice. Wash @ mealtime & end of shift. Contaminated clothing & shoes should be removed as soon as practical & thoroughly cleaned before reuse.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

## Information on Basic Physical and Chemical Properties

**Physical State** 

Paste

**Appearance** 

Clear/opaque or colored paste

Odor

Acetic Acid Odor (Vinegar

odor)

Color

Various

Odor threshold

Not determined

**Property** 

Values

Remarks • Method

рН Melting point/freezing point Boiling point/boiling range

Not determined Not determined Not determined Flash point Not applicable Evaporation rate Not determined Flammability (solid, gas) Not determined

Flammability limits in air

Page 4/8

Upper flammability limits
Lower flammability limit
Vapor pressure
Vapor density
Not determined
Not determined
Not determined
Not determined

Specific gravity ~1.04
Water solubility Not determined
Solubility in other solvents Not determined
Partition coefficient Not determined

Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity
Dynamic viscosity
Explosive properties
Oxidizing Properties

Not determined
Not determined
Not determined
Not determined
Not determined
Not determined

Other Information

Additional information Note: The above information is not intended for use in preparing product specifications

VOC Content (%) < 3%/wt (< 40 g/L)

## 10. STABILITY AND REACTIVITY

@ 25 °C (77 °F)

Reactivity

Not reactive under normal conditions

**Chemical Stability** 

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous polymerization Hazardous polymerization does not occur.

**Conditions to Avoid** 

Incompatible Materials.

**Incompatible Materials** 

Oxidizing material can cause a reaction. Water, moisture or humid air can cause hazardous vapors to form as described in Section 8

**Hazardous Decomposition Products** 

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon oxides & traces of incompletely burned carbon compounds. Silicon dioxide. Formaldehyde, Nitrogen oxides & metal oxides.

## 11. TOXICOLOGICAL INFORMATION

## Information on Likely Routes of Exposure

#### **Product Information**

Inhalation May cause irritation of respiratory tract.

**Eye Contact** May cause temporary irritation on eye contact.

Skin Contact Causes skin irritation. Can be absorbed through the skin.

Ingestion Can be harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Amorphous silica (glass) 7631-86-9	> 5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 2.2 mg/L (Rat)1 h
Polydimethylsiloxane 63148-62-9	> 17 g/kg (Rat)	> 2 g/kg(Rabbit)	-
Methyltriacetoxysilane 4253-34-3	= 2060 mg/kg (Rat)	-	-
Titanium Dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-

## Information on Physical, Chemical and Toxicological Effects

**Symptoms** 

Please see section 4 of this SDS for symptoms.

## Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

## Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen. Titanium dioxide is a possible carcinogen when it appears as a respirable dust.

Chemical Name	ACGIH	IARC	NTP	OSHA
Amorphous silica (glass) 7631-86-9		Group 3		100000000000000000000000000000000000000
Titanium Dioxide 13463-67-7		Group 2B		Х

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

## **Numerical Measures of Toxicity- Product**

Not determined

## 12. ECOLOGICAL INFORMATION

## **Ecotoxicity**

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Amorphous silica (glass) 7631-86-9	440: 72 h Pseudokirchneriella subcapitata mg/L EC50	5000: 96 h Brachydanio rerio mg/L LC50 static		7600: 48 h Ceriodaphnia dubia mg/L EC50

## Persistence and Degradability

Complete information is not yet available.

### Bioaccumulation

Complete information is not yet available.

## **Mobility**

Complete information is not yet available.

Other Adverse Effects

Not determined

## 13. DISPOSAL CONSIDERATIONS

#### **Waste Treatment Methods**

**Disposal of Wastes** 

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

**Contaminated Packaging** 

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

## 14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances

DOT

Not regulated

**IATA** 

Not regulated

IMDG

Not regulated

## 15. REGULATORY INFORMATION

## International Inventories

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

## **US Federal Regulations**

## SARA 311/312 Hazard Categories

Acute health hazard
Chronic Health Hazard
Fire hazard
Sudden release of pressure hazard
No
Reactive Hazard
No

## **US State Regulations**

Chemical Name	California Proposition 65
Titanium Dioxide - 13463-67-7	Carcinogen

### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Amorphous silica (glass)	X	X	X
7631-86-9			

Titanium Dioxide	X	X	X
13463-67-7			

### U.S. EPA Label Information

## **16. OTHER INFORMATION**

<u>NFPA</u>

**Health Hazards** 

**Flammability** 

Instability

Special Hazards
Not determined

<u>HMIS</u>

Health Hazards

Flammability

0

Physical Hazards

Not determined
Personal Protection
B- Safety Glasses,

Gloves

Issue Date

Revision Date

13-Dec-2012 01-Oct-2017

Revision Note New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



## **Safety Data Sheet**

## **BOSS® 387 Universal Silicone**

## Section 1. Identification

Product Identifier

**BOSS® 387 Universal Silicone** 

Synonyms

38720; 38701; 38700

Manufacturer Stock

03572CL10; 03572WH10; 03577CL10

Numbers

Recommended use Uses advised against Refer to Technical Information

Refer to Technical Information

Manufacturer Contact

Address

Soudal Accumetric 350 Ring Road

(270) 769-3385

Elizabethtown, KY, 42701

USA

Phone

**Emergency Phone** 

(800) 424-9300

CHEMTREC

Fax

(270) 765-2412

## Section 2. Hazards Identification

Classification

N/A

Signal Word

Pictogram

Hazard Statements

N/A

**Precautionary Statements** 

Response

N/A

Prevention

Use only outdoors or in a well-ventilated area.

Storage

N/A

Disposal

N/A

Ingredients of unknown

toxicity

0%

Hazards not Otherwise

Classified

**GHS Classification GHS Label Element** 

Not a hazardous substance or mixture. Not a hazardous substance or mixture.

Other hazards

None known

## Section 3. Ingredients

CAS	Ingredient Name	Weight %
64742-46-7	Distillates (petroleum), hydrotreated middle	20% - 30%
7631-86-9	Amorphous silica	5% - 10%

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First-Aid Measures

Comments Treat according to person's condition and specifics of exposure.

Get immediate medical attention. Only induce vomiting at the instructions of a Ingestion

physician. Never give anything by mouth to an unconscious person.

Material is not likely to present an inhalation hazard at ambient conditions. If Inhalation

material is heated or vapor are generated, care should be taken to prevent

inhalation. In case of exposure to vapor, move to fresh air.

Skin Contact Remove from skin and wash thoroughly with soap and water or waterless

cleanser. Get medical attention if irritation or other ill effects develop or persist.

Eye Contact Immediately flush with water for 15 minutes. Seek medical attention.

## Section 5. Fire Fighting Measures

Suitable Extinguishing

Media

On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire

exposed containers.

Unsuitable Extinguishing

Media

None known

Special Fire Fighting

**Procedures** 

Self-contained breathing apparatus and protective clothing should be worn when fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to

keep fire exposed containers cool.

Unusual Fire or Explosion None known

Hazards

**Products** 

Hazardous Decomposition Thermal breakdown of this product during fire or very high heat conditions may

evolve the following hazardous decomposition products:

Carbon oxides and traces of incompletely burned carbon compounds

Formaldehyde Silicon dioxide Depending on color, may also evolve: Metal oxides

## Section 6. Accidental Release Measures

Steps to be taken in case of spill or release

Observe all personal protection equipment recommendations. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

## Section 7. Handling and Storage

Handling Use adequate ventilation. Product evolves acetic acid when exposed to water

or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection. Avoid eye contact. Avoid skin contact. Avoid breathing vapors, mist, dust or fumes. Keep container

closed. Do not take internally.

Storage Use reasonable care and store away from oxidizing materials. Keep container

closed and store away from water or moisture. This material in its finely divided form presents an explosion hazard. Follow NFPA 654 (for chemical dusts) or 484 (for metal dusts) as appropriate for managing dust hazards to

minimize secondary explosion potential.

## Section 8. Exposure Controls/Personal Protection

Occupational Exposure Ingredient Name ACGIH TLV OSHA PEL STEL Limits

Distillates (petroleum), hydrotreated middle 5 mg/m3 5 mg/m3 10 mg/m3

Amorphous silica 10 mg/m3 6 mg/m3 Not Est.

Personal Protective Equipment

Goggles, Gloves

**Exposure Controls** 

Acetic acid is formed upon contact with water or humid air. Provide adequate

ventilation to control exposures within guidelines of OSHA PEL: TWA 10 ppm and ACGIH TLV: TWA 10 ppm, STEL 15 ppm.

**Engineering Controls** 

Local Ventilation: Recommended

General Ventilation: Recommended

Eye Protection

Safety goggles or glasses with side shields are recommended.

Skin Protection

Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and throughly cleaned before reuse. Chemical protective gloves are recommended.

Suitable Gloves:

Handle in accordance with good industrial hygiene and safety practices.

Respiratory Protection

Use respiratory protection unless adequate exhaust ventilation is provided or exposure assessment demonstrates that exposures are within exposure guidelines. Industrial Hygiene Personnel can assist in judging the adequacy of existing engineering controls.

Suitable Respirator:

Respiratory protection is not needed under ambient conditions.

If vapor/mist/dust/fumes are generated when material is heated or handled, respiratory protection recommended. Follow OSHA Respirator Regulations (29 CFR 1910.134) and use NIOSH/MHSA approved respirator. Protection provided by air purifying respirators against exposure to any hazardous chemical limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure level are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

**Precautionary Measures** 

Avoid eye contact. Avoid skin contact. Avoid breathing vapor, mist, dust or fumes. Keep container closed. Do not take internally. Use reasonable care.

Comment

Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection.

When heated to temperatures above 150C (300F) in the presence of air, product can form formaldehyde vapors. Physical and health hazard information is readily available on the Material Safety Data Sheet.

Note

These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions.

## Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Refer to
	product label
Odor	Acetic acid
	odor
Odor Threshold	N/A
Solubility	Not
	Determined
Partition coefficient Water/n-octanol	N/A
VOC%	24 g/L
Viscosity	Not
·	Determined
Specific Gravity	0.96
Density Ibs/Gal	N/A
Pounds per Cubic Foot	N/A

Flash Point	Not
	Applicable
FP Method	N/A
Ph	Not
	Determined
Melting Point	Not
_	Determined
Boiling Point	Not
	Determined
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	N/A
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	Not
	Determined
Vapor Density	Not
	Determined

Note

The above information is not intended for use in preparing product specifications. Contact Soudal Accumetric before writing specifications.

## Section 10. Stability and Reactivity

Materials to Avoid /

Incompatibility

Oxidizing material can cause a reaction. Water, moisture or humid air can

cause hazardous vapors to form as described in Section 8.

Conditions to Avoid

None known

Hazardous polymerization Will not occur

Chemical Stability

Stable

## Section 11. Toxicological Information

Special Hazard Information No known applicable information. on Components

## Section 12. Ecological Information

Fate and Effects in Waste

Complete information is not yet available.

Water Treatment Plants

Complete information is not yet available.

**Environmental Effects** Environmental Fate and

Complete information is not yet available.

Distribution

## Section 13. Disposal

Waste Disposal Method

We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

## Section 14. Transport Information

**UN Number** 

UN Proper Shipping Name Not regulated

**DOT Classification** Packing Group

Not regulated Not regulated

Air Shipment (IATA)

Not subject to IATA regulations.

Ocean Shipment (IMDG)

Not subject to IMDG code.

## Section 15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication

Standard 29 CFR 1910.1200.

**TSCA Status** 

All chemical substances found in this product comply with the Toxic

Substances Control Act inventory reporting requirements.

SARA Title III Section 302

Extremely Hazardous

Substances

SARA Titre III Section 304

**CERCLA Substances** 

dangereuses

SARA Title III Section 312 Hazard Class

None

None

Acute: Yes Chronic: No

Fire: No Pressure: No Reactive: No

SARA Title III Section 313

**Toxic Chemicals** 

Note

None present or none present in regulated quantities.

Chemicals are listed under the 313 Toxic Chemicals section only if they meet

or exceed a reporting threshold.

California Proposition 65

This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm:

None known

Massachusetts

Silica, amorphous (7631-86-9)

Depending on color, may also contain:

Titanium dioxide (13463-67-7)

**New Jersey** 

Dimethyl siloxane, hydroxy-terminated (70131-67-8)

Ethyltriacetoxysilane (17689-77-9)

Hydrotreated medium petroleum distillates (64742-46-7)

Methyltriacetoxysilane (4253-34-3) Silica, amorphous (7631-86-9)

Depending on color, may also contain:

Carbon black (1333-86-4) Titanium dioxide (13463-67-7)

Pennsylvania

Dimethyl siloxane, hydroxy-terminated (70131-67-8) Hydrotreated medium petroleum distillates (64742-46-7)

Silica, amorphous (7631-86-9)

Depending on color, may also contain:

Titanium dioxide (13463-67-7)

## Section 16. Other Information

**Revision Date** 

11/9/2015

Disclaimer

The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.

			1

# **Material Safety Data Sheet**

0896 (White), 0897 (Clear), 0896/50 (Aluminum Gray) HVAC/R 100% Silicone Sealant

ISDS No. 0107 Rev. 4

Emergency Phone No. 800-535-5053 - INFOTRAC

	HVAC/R 100% Sil	icone Sealant – Clear, White, Alumir	num Gray					
MANUFACTURER'S NAI TELEPHONE NUMBER	ME & Red Devil, Inc.	918-825-5744						
STREET ADDRESS	4175 Webb Street							
CITY/STATE/ZIP	Pryor, Oklahoma 7	4361						
SECTIO	N 2 – COMPOSIT	ION / HAZARDOUS I	NGREDIENTS	%	TLV	PEL	UNITS	
PRODUCT CONSISTS OF	7:							
Ethyltriacetoxys	ilane (17689-77-9)			< 6%	NE	NE		
Methyltriacetoxysilane ** (4253-34-3)				< 6%	10	10	ppm	
Titanium Dioxide *** (13463-67-7) (In white & colors only)				< 5%	10	15	mg/m3	
Silica, amorphous *** (7631-86-9)				< 13	20	20	mg/m3	
Hydroxy-terminated Dimethyl Siloxane (70131-67-8)				> 50	10	10	ppm	
Polydimethylsil	oxane (63148-62-9)			< 10	10	10	ppm	
				1				
Non-hazardous	ingredients*			> 10	NA	NA		
1910.1200). **(		rdous under the OSHA Hazard Commonmed during curing on exposure to product's physical state.	water or humid air.	1				
Calculated VOC	C: < 3%/wt (< 40 g/L). CARB	-		)N			5 - F - E =	
Calculated VOC PRIMARY ROUTE(S) OF ENTRY	C: < 3%/wt (< 40 g/L). CARB	SECTION 3 – HAZAR  Skin Absorption		<b>DN</b> ⊠ Inhala	tion	∐ Ing	estion	
Calculated VOC	C: <3%/wt (<40 g/L). CARB  Skin Contact	SECTION 3 – HAZAR	DS IDENTIFICATIO	⊠ Inhala				
PRIMARY ROUTE(S) OF ENTRY EMERGENCY	C: <3%/wt (<40 g/L). CARB  Skin Contact  Clear or colored paste. Harn irritation.  Acute: (Eye) – Direct contact	SECTION 3 – HAZAR  Skin Absorption	DS IDENTIFICATIO  Eye Contact  h skin. May cause eye & skin irrit  in) – May cause moderate irritatio	Inhala ation. May caus	e nose, throat	& respirator	y tract	
PRIMARY ROUTE(S) OF ENTRY EMERGENCY OVERVIEW EFFECTS OF	C: <3%/wt (<40 g/L). CARB  Skin Contact  Clear or colored paste. Harn irritation.  Acute: (Eye) – Direct contact	SECTION 3 — HAZAR  Skin Absorption  ful if swallowed or absorbed throug	DS IDENTIFICATIO  Eye Contact  h skin. May cause eye & skin irrit  in) – May cause moderate irritatio	Inhala ation. May caus	e nose, throat	& respirator	y tract	
PRIMARY ROUTE(S) OF ENTRY  EMERGENCY OVERVIEW  EFFECTS OF OVEREXPOSURE  MEDICAL CONDITIONS AGGRAVATED BY	C: < 3%/wt (< 40 g/L). CARB  Skin Contact  Clear or colored paste. Harn irritation.  Acute: (Eye) – Direct contact passages. (Oral) – No signif	SECTION 3 — HAZAR  Skin Absorption  If swallowed or absorbed throught may cause moderate irritation. (Skin and effects expected from a single second street of the street	DS IDENTIFICATIO  Eye Contact  h skin. May cause eye & skin irrit  in) – May cause moderate irritatio	Inhala ation. May caus	e nose, throat	& respirator	y tract	
PRIMARY ROUTE(S) OF ENTRY  EMERGENCY OVERVIEW  EFFECTS OF OVEREXPOSURE  MEDICAL CONDITIONS AGGRAVATED BY	C: < 3%/wt (< 40 g/L). CARB  Skin Contact  Clear or colored paste. Harn irritation.  Acute: (Eye) — Direct contact passages. (Oral) — No signif None known.	SECTION 3 — HAZAR  Skin Absorption  If swallowed or absorbed throught may cause moderate irritation. (Skin and effects expected from a single second street of the street	DS IDENTIFICATION  Eye Contact  h skin. May cause eye & skin irrit  in) – May cause moderate irritation short-term exposure. Prolonged/Reserved.	☑ Inhala ation. May caus n. (Inhalation) — epeated Exposur	e nose, throat Slight irritati e: No known	t & respirator	y tract tory nformation.	
PRIMARY ROUTE(S) OF ENTRY  EMERGENCY OVERVIEW  EFFECTS OF OVEREXPOSURE  MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE	C: < 3%/wt (< 40 g/L). CARB  Skin Contact  Clear or colored paste. Harn irritation.  Acute: (Eye) — Direct contact passages. (Oral) — No signif  None known.  Wash w/ soap	SECTION 3 — HAZAR  Skin Absorption  Skin Absorption  St may cause moderate irritation. (Skin and effects expected from a single strong a single strong and strong a single str	DS IDENTIFICATION  Eye Contact  h skin. May cause eye & skin irrit  in) – May cause moderate irritation short-term exposure. Prolonged/Restriction of the process of the pr	☑ Inhala ation. May caus n. (Inhalation) — epeated Exposur	e nose, throat Slight irritati e: No known	t & respirator	y tract tory nformation.	
PRIMARY ROUTE(S) OF ENTRY  EMERGENCY OVERVIEW  EFFECTS OF OVEREXPOSURE  MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE	C: < 3%/wt (< 40 g/L). CARB  Skin Contact  Clear or colored paste. Harn irritation.  Acute: (Eye) — Direct contact passages. (Oral) — No signif  None known.  Wash w/ soap	SECTION 3 – HAZAR  Skin Absorption  Skin Absorption  St may cause moderate irritation. (Skin action of the street	DS IDENTIFICATION  Eye Contact  h skin. May cause eye & skin irritation  in) — May cause moderate irritation short-term exposure. Prolonged/Reserved.  ET AID MEASURES  medical attention if symptoms per  ig least 15 minutes until irritation significant.	☑ Inhala ation. May caus n. (Inhalation) — epeated Exposur	e nose, throat Slight irritati e: No known	t & respirator	y tract tory nformation.	

	1	SECTIO	N 5 – FIRE FIO	GHTING M	TEASURES
FLAMMABLE [	Yes	⊠ No			
EXTINGUISHING MEDIA	Ci	arbon Dioxide, Dry Chemical, Foam,	Water Spray	1000000	
FLASHPOINT (°F) & METHOD		> 212 (Closed Cup)		UPPER EXPLOSIV (% BY VOLUME)	E LIMIT NE
LOWER EXPLOSIVE (% BY VOLUME)	ELIMIT	NE		AUTOIGNITION TEMPERTURE (°F	NE
UNUSUAL FIRE & EX HAZARDS	XPLOSION	None			
SPECIAL FIREFIGHTING PROCEDURES	W	exposed surfaces. Thermal I	oreakdown of this produ	ict during fire or h	equivalent) & full protective gear. Use water spray to cool nigh heat conditions may evolve the following hazardous incompletely burned carbon compounds. Formaldehyde,
		SECTION 6 -	ACCIDENTA	L RELEAS	SE MEASURES
PROCEDURES	W	ear proper protective equipment (Sec	ion 8). Use absorbent n	naterial or scrape u	up dried material & place in approved container.
		SECTI	ON 7 – HAND	LING & ST	FORAGE
HANDLING PROCED EQUIPMENT	OURES &	Keep out of reach of children & pet acetic acid when expose guidelines or use approp	d to water or humid air.	. Provide ventilati	vapors. Use w/ adequate ventilation. Product evolves on during use to control acetic acid within exposure d skin contact.
STORAGE REQUIRE	MENTS	Keep container closed & store away heated to temperatures a	r from water or moisture bove 300F in presence	e. Avoid extreme of air, product ma	heat or cold. Store away from oxidizing materials. When ay form formaldehyde vapors.
		SECTION 8 – EXPOS	SURE CONTR	OL / PERS	SONAL PROTECTION
	exposures	within guidelines of OSHA PEL: TV entilation unavailable. OSHA respirat	VA 10 ppm & ACGIG T	TLV: TWA 10 pp	Ventilation is recommended. Provide adequate ventilation to control m, STEL 15 ppm. Use respiratory protection if adequate local be followed, using NIOSH/MSHA approved respirators. Spills: Ful.
		or safety glasses w/ side shields. Avoid	l eye contact.		
CLOTHING / GLOVES	Nitrile rub	bber or butyl rubber gloves. Avoid ski	n contact.		
HYGENIC PRACTICES	Remove &	t wash contaminated clothing before	re-use. Wash hands befo	ore breaks & @ er	nd of workday.
		SECTION 9 – PH	YSICAL AND	СНЕМІС	AL PROPERTIES
PHYSICAL STATE		Viscous paste	ODO APPE	R & EARANCE	Clear or colored paste w/ acetic acid odor
SPECIFIC GRAVITY		Approximately 1.0 to 1.1		OR DENSITY	NE
EVAPORATION RATI	E	NE	BOIL	ING RANGE (°F)	NE
рН		NE	SOLU WAT	JBILITY IN ER	NE
VAPOR PRESSURE (N Hg)	им	NE	%/W (TNV	T VOLATILE )	NE
		SECTION	10 – STABILIT	ΓY AND RI	EACTIVITY
STABILITY	∠ Yes	No Stable under normal co			
INCOMPATABILITY			als to Avoid: Water, mouse a reaction.	oisture or humid a	iir can cause hazardous vapors to form (Sec. 8). Oxidizing material
CONDITIONS NOTO AVOID	one.				
HAZARDOUS POLYMERIZATION/F DECOMPOSITION PR		Hazardous polymerization wil	l not occur under norma	al conditions. Nor	mal decomposition products, ie: COx, NOx.

ACGIH	No known applicable information. This product does not conta	ain carcinogens	(@0.1% or grea	iter) as defined by IARC, NTP or OSHA.		
OSHA	No known applicable information. See above.					
P.C	No known applicable information. See above.					
NTP	No known applicable information. See above.					
ATA WITH POSSIBLE RELEVANCE TO HUMA	No known applicable information. See above.					
And the second s	SECTION 12 – ECOLOG	GICAL IN	IFORMA'	ΓΙΟΝ		
AQUATIC TOXICITY	Complete information is not yet available.					
	Ecotoxicity Classification Criteria:					
	Hazard Parameters (LC50 or EC50) High	Me	edium	Low		
	Acute Aquatic Toxicity mg/L <= 1	>1	& <= 100	>100		
	Acute Terrestrial Toxicity <= 100	> i	00 & <=2000	>2000		
	(Table adapted from "Environmental Toxicology & Risk A	Assessment", A	STM STP 1179,	p. 34, 1993)		
	(Table can be used to classify the ecotoxicity of this produc the section concerning the overall ecological safety of this		icity data is liste	d above. Please read the other information presented		
	SECTION 13 – DISPOSA	AL CONS	SIDERAT	IONS		
WASTE DISPOSAL	Dispose of material in accordance w/ Federal, State & Loc	Dispose of material in accordance w/ Federal, State & Local regulations.				
EPA WASTE CODE IF DISCARDED (40CFR Sec.261)  None. RCRA Hazard Class (40 CFR 261): Not classified as a hazardous waste. State or local laws may impose additional regulatory requirements regarding disposal.						
	SECTION 14 – TRANS	PORT IN	FORMAT	ION		
SPECIAL SHIPPING INFORMATION	DOT Road Shipment Information (49 CFR 172.101): Not (IATA): Not subject to IATA regulations.	subject to DOT	Cocean Shipme	nt (IMDG): Not subject to IMDG code. <u>Air Shipmen</u>		
	SECTION 15 – REGULA	ATORY I	NFORMA	TION		
CERCLA – SARA ''AZARD TEGORY	Section 304 CERCLA: None. Section 302 (Extremely Hazardous Substances): None. Section 312 (Hazard Class): Acute: Yes. Chronic: No. Fire: No. Pressure: No. Reactive: No.	U.S. STATE REGS	See Section 16	•		
SARA 313	None present or none present in regulated quantities.	TSCA	All ingredients	either on TSCA Inventory or exempt.		
	SECTION 16 – OTHER INFORMATION	\ N/SPEC	AL PREC	CAUTIONS / LEGEND		
Silica, amorphous (76 (Non-Haz @ >3%): I	(Known to State of California to cause cancer) None. NJ Right-to-631-86-9), Methyltriacetoxysilane (4253-34-3), Ethyltriacetoxysila Dimethyl siloxane, hydroxy-terminated (70131-67-8) Ingredients Kammability: 1, Reactivity: 0. Product colors other than white, may o	ne (17689-77-9 Inown to State	), Polydimethyle of California to o	siloxane (63148-62-9). <u>Pennsylvania Right-to-Know</u> cause birth defects or reproductive harm: None. <u>NFP</u>		

<u>LEGEND</u>: NA – Not Applicable, NE – Not Established, UN – Unavailable, VOC – Volatile Organic Compound, PEL – Permissible Exposure Limit, TLV – Threshold Limit Value, STEL – Short Term Exposure Limit, MSDS – Material Safety Data Sheet, ACGIH – American Conference of Governmental Industrial Hygienists, SARA – Superfund Amendments & Reauthorization Act of 1986, OSHA – Occupational Safety & Health Administration, HMIS – Hazardous Materials Identification System, NTP – National Toxicology Program, CEIL – Ceiling Exposure Limit, CASRN (CAS Number) – Chemical Abstracts Service Registry Number, TSCA – Toxic Substances Control Act, NFPA – National Fire Protection Association.

Reviewed By: Larry G. Brandon	VP Technology & General Manager	March 13, 2012
NAME	TITLE	DATE

The information contained herein has been developed based upon currently available scientific data. New information may be developed from time to time which may render the conclusions this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or for the consequences of its use or misuse.

		<i>.</i>



## Safety Data Sheet acc. to ISO 11014

Version number 1

Reviewed on 05/18/2015

#### 1 Identification

- · Product identifier
- · Trade name:

FS-ONE MAX

Hilti Firestop Filler Mastic CFS-FIL

- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Construction chemicals
- · Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

5400 South 122nd East Ave.

US-Tulsa, OK 74146 Phone: (800) 879-8000 Fax: (800) 879-7000

Español: (800) 879-5000

· Information department:

chemicals.hse@hilti.com see section 16

· Emergency telephone number:

Chem-Trec

Tel.: 1 800 424 9300

Tox Info Suisse - 24 h Service

Tel.: 0041 / 44 251 51 51 (international)

## 2 Hazard(s) identification

- · Classification of the substance or mixture The product is not classified according to the Globally Harmonized System (GHS).
- · Label elements
- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Classification system
- · NFPA ratings (scale 0-4)



Health = 0Fire = 0Reactivity = 0

- Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.

### 3 Composition/information on ingredients

- Chemical characterization: Mixtures
- · Description:

Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

57-55-6 propane-1,2-diol

<2.5%

Additional information For the wording of the listed risk phrases refer to section 16.

## 4 First-aid measures

- · Description of first aid measures
- · General information No special measures required.
- · After inhalation Take affected persons into fresh air and keep quiet. · After skin contact Immediately wash with water and soap and rinse thoroughly.
- · After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor,
- · After swallowing Seek immediate medical advice.
- · Information for doctor
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.



## Safety Data Sheet acc. to ISO 11014

Version number 1

Reviewed on 05/18/2015

(Contd. of page 1)

· Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbondioxide (CO2)

· Advice for firefighters

· Protective equipment: Ensure adequate ventilation

## 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

Particular danger of slipping on leaked/spilled product.

· Environmental precautions: Do not allow product to reach sewage system or any water course.

· Methods and material for containment and cleaning up:

Pick up mechanically.

Dispose contaminated material as waste according to item 13.

· Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- ·Handling
- · Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles; keep containers securely closed and dry, store at 5 25 °C / 41 77 °F
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Storage class 10
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

57-55-6 propane-1,2-diol

WEEL Long-term value: 10 mg/m³

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures for handling chemicals should be followed.

Avoid contact with the eyes and skin.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

- · Breathing equipment: Not necessary if room is well-ventilated.
- · Protection of hands:



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation EN 374

· Material of gloves

Synthetic gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable: Nitrile rubber, NBR

(Contd. on page 3)





## Safety Data Sheet acc. to ISO 11014

Version number 1

Reviewed on 05/18/2015

(Contd. of page 2)

· Eye protection:



Tightly sealed goggles.

EN 166 + EN 170

· Body protection:



Protective work clothing.

Physical and chemical prope	erties
· Information on basic physical and c	hemical properties
· General Information	• •
· Appearance:	
Form:	Pasty Red
Color: · Odor:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	Not applicable
· Flammability (solid, gaseous)	Not applicable.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined,
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17 mm Hg)
· Density:	Not determined
· Relative density	Not determined.
· Vapour density	Not determined.
<b>7</b>	Not applicable, Not determined.
· Evaporation rate	Not determined,
Solubility in / Miscibility with	Not miscible or difficult to mix
Water:	
· Partition coefficient (n-octanol/wat	er); Not determined.
· Viscosity:	Y-1 1-1
dynamic:	Not determined. Not determined.
kinematic:	rvot determined,
· Solvent content:	1,0 %
Organic solvents: Water:	18.5 %
· Other information	VOC Content: 9 g/l (EPA Method 24)

## 10 Stability and reactivity

- ·Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known
- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known

1



## Safety Data Sheet acc. to ISO 11014

Version number 1

Reviewed on 05/18/2015

(Contd. of page 3)

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
  on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

Additional toxicological information:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

· IARC (International Agency for Research on Cancer)

14808-60-7 Quartz (SiO2)

· NTP (National Toxicology Program)

14808-60-7 Quartz (SiO2)

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Results of PBT and vPvB assessment PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- Waste treatment methods
- · Recommendation Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- European waste catalogue:
- 08 00 00
- 08 04 00
- 08 04 10
- · Uncleaned packagings:
- · Recommendation: Dispose of packaging according to regulations on the disposal of packagings.

UN-Number		
DOT, ADR, ADN, IMDG, IATA	Void	
UN proper shipping name DOT, ADR, ADN, IMDG, IATA	Void	
Transport hazard class(es)		
DOT, ADR, ADN, IMDG, IATA Class	Void	
Packing group DOT, ADR, IMDG, IATA	Void	
Environmental hazards: Marine pollutant:	No	
· Special precautions for user	Not applicable.	
Transport in bulk according to Annex II of MAI the IBC Code	RPOL73/78 and Not applicable,	
· UN "Model Regulation":		

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Section 355 (Extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 5)

		,	



## **Safety Data Sheet** acc. to ISO 11014

Version number 1

Reviewed on 05/18/2015

	(Contd. of page 4)
Section 313 (Specific toxic chemical listings):	
None of the ingredients are listed.	
· TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
· Proposition 65:	
· Chemicals known to cause cancer:	
14808-60-7 Quartz (SiO2)	
· Cancerogenity categories	
· EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
· TLV (Threshold Limit Value established by ACGIH)	
14808-60-7 Quartz (SiO2)	A2
· MAK (German Maximum Workplace Concentration)	
14808-60-7 Quartz (SiO2)	1
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
14808-60-7 Quartz (SiO2)	
Chemical safety assessment: not required.	•

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Department issuing SDS:

Hilti Corporation Business Unit Chemicals Quality/Safety/Environment FL-9494 Schaan / Liechtenstein

chemicals.hse@hilti.com Tel.: +423 234 3004 FAX.: +423 234 3462

 $\cdot$  Date of preparation / last revision 05/18/2015 / -

Date of preparation / last revision 05/18/2015 / 
Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Marinime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

\* Data compared to the previous version altered.

•			
		•	



Revision Number: 003.0

Issue date: 03/04/2015

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

LOC 10oz PL400 ALL WEATHER 12SC IDH number:

1907194

Product type:

Water based adhesive

Region:

**United States** 

Restriction of Use: Company address: None identified

Contact information:

Henkel Corporation

Telephone: +1 (800) 624-7767

One Henkel Way

Rocky Hill, Connecticut 06067

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

## 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

WARNING:

ABRASION COULD RELEASE RESPIRABLE PARTICLES OF SILICA QUARTZ, A CANCER HAZARD BY INHALATION, NORMAL USE OF THIS PRODUCT CAUSES NO SUCH RELEASE.

FLAMMABLE LIQUID AND VAPOR. CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	3
EYE IRRITATION	2A





#### **Precautionary Statements**

Prevention:

Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Wear

protective gloves, eye protection, and face protection.

Response:

If on skin (or hair): Take off immediately all contaminated clothing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. If eye irritation persists: Get medical attention. In case of fire; Use

foam, dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

IDH number: 1907194

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Limestone	1317-65-3	30 - 60	
Acetone	67-64-1	1-5	
Kaolin	1332-58-7	1 - 5	***************************************
Urea	57-13-6	1-5	
Ethanol	64-17-5	1 - 5	
Quartz (SiO2)	14808-60-7	0.1 - 1	

<sup>\*</sup> Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

Inhalation:

Move to fresh air in case of accidental inhalation of vapours.

Skin contact:

Wash affected area immediately with soap and water.

Eye contact:

Immediately flush eyes with plenty of water for at least 15 minutes. If

symptoms develop and persist, get medical attention.

Ingestion:

Consult a physician if necessary.

Symptoms:

See Section 11.

## 5. FIRE FIGHTING MEASURES

Extinguishing media:

Carbon dioxide, foam, powder Water fog.

Special firefighting procedures:

Use water spray to keep fire exposed containers cool and disperse vapors. Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards:

Closed containers may rupture (due to build up of pressure) when exposed to

extreme heat.

Hazardous combustion products:

Oxides of carbon. Oxides of nitrogen.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** 

Not available.

Clean-up methods:

Absorb spill with inert material. Shovel material into appropriate container for

disposal. Remove all sources of ignition.

## 7. HANDLING AND STORAGE

Handling:

Avoid prolonged or repeated skin contact with this material. Keep away from sources of ignition - no smoking. Keep out of the reach of children.

Storage:

For safe storage, store at or above 0 °C (32°F)

Keep from freezing. Store in a cool, dry area. Keep containers closed when

not in use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

IDH number: 1907194

Product name: LOC 10oz PL400 ALL WEATHER 12SC

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Acetone	750 ppm STEL 500 ppm TWA	1,000 ppm (2,400 mg/m3) PEL	None	None
Kaolin	2 mg/m3 TWA Respirable fraction.	15 mg/m3 PEL Total dust. 5 mg/m3 PEL Respirable fraction.	None	None
Urea	None	None	10 mg/m3 TWA Total particulate.	None
Ethanol	1,000 ppm STEL	1,000 ppm (1,900 mg/m3) PEL	None	None
Quartz (SiO2)	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	None

**Engineering controls:** 

Use local ventilation if general ventilation is insufficient to maintain vapor

concentration below established exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Use impermeable gloves and protective clothing as necessary to prevent skin

contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Color:

Odor:

Odor threshold:

pH:

. Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity:

Vapor density: Flash point:

Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate:

Solubility in water: Partition coefficient (n-octanol/water):

VOC content:

IDH number: 1907194

Viscosity:

Paste Off white

Acrylic Not available.

7 - 9

Not available. 100 °C (212°F) Not available.

1.335 Not available.

40 °C (104°F) Not available. Not available.

Not available. Not available. Not available.

Not available.

1.5 %; 50 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method)

200,000 cp

Not available.

Decomposition temperature:

## 10. STABILITY AND REACTIVITY

Stability:

Stable under normal conditions of storage and use.

Hazardous reactions:

Will not occur.

Hazardous decomposition

products:

Oxides of carbon. Oxides of nitrogen.

Incompatible materials:

None known

Reactivity:

Not available.

Conditions to avoid:

Heat. Do not freeze.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Inhalation, Skin contact, Eye contact

### Potential Health Effects/Symptoms

Inhalation:

May cause irritation to nose and throat. Inhalation of high vapor concentrations may produce respiratory irritation, and may cause central nervous system (CNS) depression. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.

Skin contact:

May cause moderate skin irritation.

Eye contact:

May cause slight irritation to eyes on contact.

Ingestion:

Not expected to be harmful by ingestion. Ingestion of large amounts may produce

gastrointestinal disturbances including irritation, nausea, and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Limestone	None	Nuisance dust	
Acetone	Oral LD50 (RABBIT) = 5,340 mg/kg Oral LD50 (RAT) = 5,800 mg/kg Oral LD50 (RAT) = 9,800 mg/kg Dermal LD50 (RABBIT) = 20,000 mg/kg Inhalation LC50 (RAT, 8 h) = 50.1 mg/l Inhalation LC50 (RAT, 4 h) = 76 mg/l	Blood, Central nervous system, Irritant, Reproductive	
Kaolin	Oral LD50 (RAT) = > 5,000 mg/kg Dermal LD50 (RAT) = > 5,000 mg/kg	Nuisance dust	
Urea	Oral LD50 (RAT) = 8,471 mg/kg	Central nervous system, Irritant, Metabolic	
Ethanol	Oral LD50 (RAT) = 9.9 g/kg Oral LD50 (RAT) = 6.2 g/kg Oral LD50 (RAT) = 17.8 g/kg Oral LD50 (RAT) = 11.5 g/kg Oral LD50 (RAT) = 10.6 g/kg Oral LD50 (RAT) = 7,060 mg/kg Inhalation LC50 (RAT, 10 h) = 20000 ppm	Central nervous system, Irritant	
Quartz (SiO2)	None	Immune system, Lung, Some evidence of carcinogenicity	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Acetone	No	No	No
Kaolin	No	No	No
Urea	No	No	No
Ethanol	No	No	No
Quartz (SiO2)	Known To Be Human Carcinogen.	Group 1	No

IDH number: 1907194 Product name: LOC 10oz PL400 ALL WEATHER 12SC

## 12. ECOLOGICAL INFORMATION

**Ecological information:** 

Not available.

#### DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number:

It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics

Leaching Procedure (TCLP) 40 CFR 261.20-24.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:

Adhesives

Hazard class or division:

Identification number:

**UN 1133** 

Packing group:

International Air Transportation (ICAO/IATA)

Proper shipping name:

Adhesives

Hazard class or division:

Identification number:

UN 1133

Packing group:

Water Transportation (IMO/IMDG)

Proper shipping name:

**ADHESIVES** 

Hazard class or division:

UN 1133

Identification number: Packing group:

## 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status:

All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification:

None above reporting de minimis

CERCLA/SARA Section 302 EHS:

CERCLA/SARA Section 311/312:

None above reporting de minimis Fire, Immediate Health, Delayed Health

**CERCLA/SARA Section 313:** 

None above reporting de minimis

California Proposition 65:

This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

IDH number: 1907194

**CEPA DSL/NDSL Status:** 

All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: Corrected information in Section(s): 2

Prepared by:

Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

Issue date:

03/04/2015

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

### 1 Identification

· Product identifier

· Trade name: <u>EVERseal</u> EZseal

- · Other means of identification: No other identifiers
- · Recommended use and restriction on use
- · Recommended use: Water based sealant
- · Restrictions on use: No relevant information available.
- Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Ductmate Industries, Inc.

210 5th St.

Charleroi, PA 15022 Phone: 800-990-8459

· Emergency telephone number:

ChemTel

(800)255-3924 (North America) +1 (813)248-0585 (International)



# 2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified as hazardous according to the Globally Harmonized System (GHS).

- · Label elements
- · GHS label elements Not regulated.
- · Hazard pictograms: Not regulated.
- · Signal word: Not regulated.
- · Hazard statements: Not regulated.
- · Precautionary statements: Not regulated.
- · Other hazards There are no other hazards not otherwise classified that have been identified.

### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:	
1317-65-3 Limestone	10-40%
14807-96-6 Talc	10-40%
57-55-6 Propylene glycol	<5%

· Additional information: For the wording of the listed Hazard Statements, refer to section 16.

#### 4 First-aid measures

- Description of first aid measures
- · After inhalation:

Respiration of particulates is unlikely during normal usage.

(Cont'd. on page 2)

Page: 2/8

# **Safety Data Sheet**

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: EVERseal EZseal

(Cont'd. of page 1)

Supply fresh air and to be sure to call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed:

Nausea in case of ingestion.

May cause gastro-intestinal irritation if ingested.

· Indication of any immediate medical attention and special treatment needed: Treat symptomatically.

### 5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:

The product is not flammable.

Use fire fighting measures that suit the environment.

- · For safety reasons unsuitable extinguishing agents: None.
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Use personal protective equipment as required.

- · Environmental precautions Avoid release to the environment.
- Methods and material for containment and cleaning up

Towel or mop up material and collect in a suitable container.

For larger spills, add sawdust, chalk or other inert binding material, then sweep up and discard.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7 Handling and storage

(Cont'd. on page 3)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: EVERseal EZseal

(Cont'd. of page 2)

- ·Handling
- · Precautions for safe handling:

Use only in well ventilated areas.

Avoid contact with the eyes and skin.

- · Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles.

Information about storage in one common storage facility:

Store away from oxidizing agents. Store away from foodstuffs.

· Specific end use(s) No relevant information available.

## 8 Exposure controls/personal protection

· Control parameters

Control paran	leters — — — — — — — — — — — — — — — — — — —
· Components w	ith limit values that require monitoring at the workplace:
1317-65-3 Lime	stone
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn
14807-96-6 Talo	
PEL (USA)	Long-term value: 20 mppcf ppm (containing <1% Quartz)
REL (USA)	Long-term value: 2* mg/m³ *respirable dust; and <1% Quartz
TLV (USA)	Long-term value: 2* mg/m³ *as respirable fraction; E
EL (Canada)	Long-term value: 2 *0.1 f/cc mg/m³ resp. *if contains asbestos : ACGIH A1, IARC 1
EV (Canada)	Long-term value: 2* mg/m³, 2 f/cc ppm *respirable
LMPE (Mexico)	Long-term value: 2* mg/m³ A4, *fracción respirable
57-55-6 Propyle	ene glycol
WEEL (USA)	Long-term value: 10 mg/m³
EV (Canada)	Long-term value: 155* 10** mg/m³, 50* ppm *vapour and aerosol;**aerosol only

- · Exposure controls
- General protective and hygienic measures:

Avoid contact with the eyes and skin.

Keep away from foodstuffs, beverages and feed.

(Cont'd. on page 4)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: EVERseal EZseal

(Cont'd. of page 3)

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash hands before breaks and at the end of work.

- · Engineering controls: No relevant information available.
- · Breathing equipment:

Not required under normal conditions of use.

A NIOSH approved dust respirator should be used for operations generating dust.

Protection of hands:

Gloves are advised for repeated or prolonged contact.

Wear protective gloves to handle contents of damaged or leaking units.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Eye protection: Follow relevant national guidelines concerning the use of protective eyewear.
- · Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment

Avoid release to the environment.

· Risk management measures No relevant information available.

Information on basic physical:	and chemical properties	
Appearance:	• •	
Form:	Liquid	
Color:	Gray	
Odor:	Mild	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Melting point/Melting range:	Not determined.	
Boiling point/Boiling range:	Not determined.	
Flash point:	Not applicable.	
·	The product is not flammable.	
Flammability (solid, gaseous):	Not determined.	
Auto-ignition temperature:	Not determined.	
Decomposition temperature:	Not determined.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
Oxidizing properties:	Non-oxidizing.	
Vapor pressure:	Not determined.	
Density:		
Relative density:	1.35±0.04	
Vapor density:	Not determined.	
Evaporation rate:	Not determined.	

Page: 5/8

# **Safety Data Sheet**

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: EVERseal EZseal

(Cont'd. of page 4)

· Solubility in / Miscibility with

Water:

Soluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity

Dynamic:

Not determined.

Kinematic:

Not determined.

Other information

No relevant information available.

### 10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability:
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions Reacts with strong oxidizing agents.
- · Conditions to avoid Excessive heat.
- · Incompatible materials Oxidizers
- · Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- · On the skin: Based on available data, the classification criteria are not met.
- · On the eve: Based on available data, the classification criteria are not met.
- · Sensitization: Based on available data, the classification criteria are not met.
- · IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Eye contact.

Skin contact.

· Germ cell mutagenicity: Based on available data, the classification criteria are not met.

(Cont'd. on page 6)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: EVERseal EZseal

(Cont'd. of page 5)

- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

# 12 Ecological information

- · Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.
- Other adverse effects No relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

Transport information		
UN-Number DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
UN proper shipping name DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
Transport hazard class(es)	7.000	
DOT, ADR/RID/ADN, IMDG, IATA		
Class	Not regulated.	
Packing group	Nl. 4	
DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
Environmental hazards		
Marine pollutant:	No	
Special precautions for user	Not applicable.	
		(Cont'd. on pag

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: EVERseal EZseal

(Cont'd. of page 6)

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not a

Not applicable.

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

Reference to talc not applicable to product, as product contains no asbestiform fibers.

14807-96-6 Talc

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· Canadian Domestic Substances List (DSL):

All ingredients are listed or exempt.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

(Cont'd. on page 8)

Page: 8/8

# **Safety Data Sheet**

### according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: EVERseal EZseal

(Cont'd. of page 7)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

#### · Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtel.com

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

#### 1 Identification

· Product identifier

· Trade name: <u>Proseal</u> Fiberseal

- · Other means of identification: No other identifiers
- · Recommended use and restriction on use
- · Recommended use: Water based sealant
- · Restrictions on use: No relevant information available.
- Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Ductmate Industries, Inc.

210 5th St.

Charleroi, PA 15022 Phone: 800-990-8459



ChemTel

(800)255-3924 (North America) +1 (813)248-0585 (International)



## 2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified as hazardous according to the Globally Harmonized System (GHS).

- · Label elements
- · GHS label elements Not regulated.
- · Hazard pictograms: Not regulated.
- · Signal word: Not regulated.
- · Hazard statements: Not regulated.
- · Precautionary statements: Not regulated.
- · Other hazards There are no other hazards not otherwise classified that have been identified.

## 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:		
1317-65-3	Limestone	10-40%
14807-96-6	Talc	10-40%
57-55-6	Propylene glycol	<5%

· Additional information: For the wording of the listed Hazard Statements, refer to section 16.

#### 4 First-aid measures

- Description of first aid measures
- · After inhalation:

Respiration of particulates is unlikely during normal usage.

(Cont'd. on page 2)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: Proseal Fiberseal

(Cont'd. of page 1)

Supply fresh air and to be sure to call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed:

Nausea in case of ingestion.

May cause gastro-intestinal irritation if ingested.

Indication of any immediate medical attention and special treatment needed: Treat symptomatically.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

The product is not flammable.

Use fire fighting measures that suit the environment.

- · For safety reasons unsuitable extinguishing agents: None.
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

#### 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Use personal protective equipment as required.

- · Environmental precautions Avoid release to the environment.
- · Methods and material for containment and cleaning up

Towel or mop up material and collect in a suitable container.

For larger spills, add sawdust, chalk or other inert binding material, then sweep up and discard.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

(Cont'd. on page 3)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: Proseal Fiberseal

(Cont'd. of page 2)

- ·Handling
- · Precautions for safe handling:

Use only in well ventilated areas.

Avoid contact with the eyes and skin.

- · Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles.

Information about storage in one common storage facility:

Store away from oxidizing agents.

Store away from foodstuffs.

· Specific end use(s) No relevant information available.

## 8 Exposure controls/personal protection

· Control parameters

Control paran	
· Components w	ith limit values that require monitoring at the workplace:
1317-65-3 Lime	stone
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn
14807-96-6 Talo	
PEL (USA)	Long-term value: 20 mppcf ppm (containing <1% Quartz)
REL (USA)	Long-term value: 2* mg/m³ *respirable dust; and <1% Quartz
TLV (USA)	Long-term value: 2* mg/m³ *as respirable fraction; E
EL (Canada)	Long-term value: 2 *0.1 f/cc mg/m³ resp. *if contains asbestos : ACGIH A1, IARC 1
EV (Canada)	Long-term value: 2* mg/m³, 2 f/cc ppm *respirable
LMPE (Mexico)	Long-term value: 2* mg/m³ A4, *fracción respirable
57-55-6 Propyle	ene glycol
WEEL (USA)	Long-term value: 10 mg/m³
EV (Canada)	Long-term value: 155* 10** mg/m³, 50* ppm *vapour and aerosol;**aerosol only

- · Exposure controls
- General protective and hygienic measures:

Avoid contact with the eyes and skin.

Keep away from foodstuffs, beverages and feed.

(Cont'd. on page 4)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: Proseal Fiberseal

(Cont'd. of page 3)

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash hands before breaks and at the end of work.

- · Engineering controls: No relevant information available.
- · Breathing equipment:

Not required under normal conditions of use.

A NIOSH approved dust respirator should be used for operations generating dust.

Protection of hands:

Gloves are advised for repeated or prolonged contact.

Wear protective gloves to handle contents of damaged or leaking units.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- Eye protection: Follow relevant national guidelines concerning the use of protective eyewear.
- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment

Avoid release to the environment.

· Risk management measures No relevant information available.

Information on basic physical a	and chemical properties	
Appearance:		
Form:	Liquid	
Color:	Gray	
Odor:	Mild	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Melting point/Melting range:	Not determined.	
Boiling point/Boiling range:	Not determined.	
Flash point:	Not applicable.	
	The product is not flammable.	
Flammability (solid, gaseous):	Not determined.	
Auto-ignition temperature:	Not determined.	
Decomposition temperature:	Not determined.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits	10.444	
Lower:	Not determined.	
Upper:	Not determined.	
Oxidizing properties:	Non-oxidizing.	
Vapor pressure:	Not determined.	
Density:		
Relative density:	1.35±0.04	
Vapor density:	Not determined.	
Evaporation rate:	Not determined.	

Page: 5/8

# **Safety Data Sheet**

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: Proseal Fiberseal

(Cont'd. of page 4)

· Solubility in / Miscibility with

Water: Soluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity

Dynamic: Not determined. Kinematic: Not determined.

• Other information No relevant information available.

### 10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability:
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions Reacts with strong oxidizing agents.
- · Conditions to avoid Excessive heat.
- · Incompatible materials Oxidizers
- · Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

### 11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- · On the skin: Based on available data, the classification criteria are not met.
- · On the eye: Based on available data, the classification criteria are not met.
- · Sensitization: Based on available data, the classification criteria are not met.
- · IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Eye contact.

Skin contact.

· Germ cell mutagenicity: Based on available data, the classification criteria are not met.

(Cont'd, on page 6)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: Proseal Fiberseal

(Cont'd, of page 5)

- · Carcinogenicity: Based on available data, the classification criteria are not met.
- Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.
- · Other adverse effects No relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
UN proper shipping name DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
Transport hazard class(es)		
DOT, ADR/RID/ADN, IMDG, IATA		
Class	Not regulated.	
Packing group		
DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
Environmental hazards		
Marine pollutant:	No	
Special precautions for user	Not applicable.	

Page: 7/8

# **Safety Data Sheet**

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: Proseal Fiberseal

(Cont'd. of page 6)

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

- · Proposition 65 (California)
- Chemicals known to cause cancer:

Reference to talc not applicable to product, as product contains no asbestiform fibers.

14807-96-6 Talc

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· Canadian Domestic Substances List (DSL):

All ingredients are listed or exempt.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

(Cont'd, on page 8)

Page: 8/8

# **Safety Data Sheet**

### according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: Proseal Fiberseal

(Cont'd. of page 7)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

#### · Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtel.com

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

#### 1 Identification

- · Product identifier
- · Trade name: Lag-It
- · Other means of identification: No other identifiers
- · Recommended use and restriction on use
- · Recommended use: Water based adhesive
- · Restrictions on use: No relevant information available.
- Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Ductmate Industries, Inc.

210 5th St.

Charleroi, PA 15022 Phone: 800-990-8459

· Emergency telephone number:

ChemTel

(800)255-3924 (North America)

+1 (813)248-0585 (International)



### 2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified as hazardous according to the Globally Harmonized System (GHS).

- · Label elements
- · GHS label elements Not regulated.
- · Hazard pictograms: Not regulated.
- · Signal word: Not regulated.
- · Hazard statements: Not regulated.
- · Precautionary statements: Not regulated.
- · Other hazards There are no other hazards not otherwise classified that have been identified.

### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components	);	
1317-65-3	Limestone	10-40%
14807-96-6	Talc	10-40%
57-55-6	Propylene glycol	<5%
	4-Nonylphenol, branched, ethoxylated	<5%
	♦ Acute Tox. 4, H302; Eye Irrit. 2A, H319	
13463-67-7	Titanium dioxide	<5%

· Additional information:

For the wording of the listed Hazard Statements, refer to section 16.

Non-classification as a carcinogen is based on non-inhalable form of product. IARC listings for TiO2 note that the substance must be respirable.

Page: 2/8

# **Safety Data Sheet**

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: Lag-It

(Cont'd, of page 1)

#### 4 First-aid measures

### · Description of first aid measures

· After inhalation:

Respiration of particulates is unlikely during normal usage.

Supply fresh air and to be sure to call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· Most important symptoms and effects, both acute and delayed:

Nausea in case of ingestion.

May cause gastro-intestinal irritation if ingested.

· Indication of any immediate medical attention and special treatment needed: Treat symptomatically.

## 5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:

The product is not flammable.

Use fire fighting measures that suit the environment.

- · For safety reasons unsuitable extinguishing agents: None.
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

#### 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Use personal protective equipment as required.

- · Environmental precautions Avoid release to the environment.
- · Methods and material for containment and cleaning up

Towel or mop up material and collect in a suitable container.

For larger spills, add sawdust, chalk or other inert binding material, then sweep up and discard.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Page: 3/8

# **Safety Data Sheet**

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: Lag-It

(Cont'd. of page 2)

# 7 Handling and storage

- ·Handling
- · Precautions for safe handling:

Use only in well ventilated areas.

Avoid contact with the eyes and skin.

- · Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles.

Information about storage in one common storage facility:

Store away from oxidizing agents.

Store away from foodstuffs.

· Specific end use(s) No relevant information available.

## 8 Exposure controls/personal protection

Control paran	
· Components w	ith limit values that require monitoring at the workplace:
1317-65-3 Lime	stone
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn
14807-96-6 Talo	
PEL (USA)	Long-term value: 20 mppcf ppm (containing <1% Quartz)
REL (USA)	Long-term value: 2* mg/m³ *respirable dust; and <1% Quartz
TLV (USA)	Long-term value: 2* mg/m³ *as respirable fraction; E
EL (Canada)	Long-term value: 2 *0.1 f/cc mg/m³ resp. *if contains asbestos : ACGIH A1, IARC 1
EV (Canada)	Long-term value: 2* mg/m³, 2 f/cc ppm *respirable
LMPE (Mexico)	Long-term value: 2* mg/m³ A4, *fracción respirable
57-55-6 Propyle	ene glycol
WEEL (USA)	Long-term value: 10 mg/m³
EV (Canada)	Long-term value: 155* 10** mg/m³, 50* ppm *vapour and aerosol;**aerosol only
13463-67-7 Tita	nium dioxide
PEL (USA)	Long-term value: 15* mg/m³ *total dust
	(Cont'd. on page 4

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: Lag-It

		(Cont'd. of page 3)
REL (USA)	See Pocket Guide App. A	
TLV (USA)	Long-term value: 10 mg/m³	
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction; IARC 2B	
EV (Canada)	Long-term value: 10 mg/m³ total dust	
LMPE (Mexico)	Long-term value: 10 mg/m³ A4	

- Exposure controls
- · General protective and hygienic measures:

Avoid contact with the eyes and skin.

Keep away from foodstuffs, beverages and feed.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash hands before breaks and at the end of work.

- · Engineering controls: No relevant information available.
- · Breathing equipment:

Not required under normal conditions of use.

A NIOSH approved dust respirator should be used for operations generating dust.

Protection of hands:

Gloves are advised for repeated or prolonged contact.

Wear protective gloves to handle contents of damaged or leaking units.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- Eye protection: Follow relevant national guidelines concerning the use of protective eyewear.
- · Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment

Avoid release to the environment.

· Risk management measures No relevant information available.

Information on basic physical a	and chemical properties	
Appearance:		
Form:	Liquid	
Color:	White	
Odor:	Mild	
Odor threshold:	Not determined.	
pH-value:	Not determined.	AND THE PROPERTY OF THE PROPER
Melting point/Melting range:	Not determined.	
Boiling point/Boiling range:	Not determined.	
Flash point:	Not applicable.	
·	The product is not flammable.	
Flammability (solid, gaseous):	Not determined.	
Auto-ignition temperature:	Not determined.	
Decomposition temperature:	Not determined.	

Page: 5/8

# **Safety Data Sheet**

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: Lag-It

		(Cont'd. of page
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
Oxidizing properties:	Non-oxidizing.	
· Vapor pressure:	Not determined.	
· Density:		
Relative density:	1.35±0.04	
Vapor density:	Not determined.	
Evaporation rate:	Not determined.	
· Solubility in / Miscibility with		
Water:	Soluble.	
· Partition coefficient (n-octanol/wat	ter): Not determined.	
· Viscosity		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Other information	No relevant information available.	

# 10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability:
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions Reacts with strong oxidizing agents.
- · Conditions to avoid Excessive heat.
- · Incompatible materials Oxidizers
- · Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

### 11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.
- LD/LC50 values that are relevant for classification:
   127087-87-0 4-Nonylphenol, branched, ethoxylated
   Oral LD50 1410 mg/kg (rat)
   Dermal LD50 2830 mg/kg (rabbit)
  - · Primary irritant effect:
  - · On the skin: Based on available data, the classification criteria are not met.

(Cont'd. on page 6)

Page: 6/8

# **Safety Data Sheet**

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: Lag-It

(Cont'd. of page 5)

- · On the eye: Based on available data, the classification criteria are not met.
- · Sensitization: Based on available data, the classification criteria are not met.
- · IARC (International Agency for Research on Cancer):

Reference to titanium dioxide is based on unbound respirable particles and is not applicable to the product as supplied.

13463-67-7 Titanium dioxide

2B

#### · NTP (National Toxicology Program):

None of the ingredients are listed.

# · OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Eve contact.

Skin contact.

- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity:

Contains known or suspect carcinogens when inhaled. Product is in non-inhalable form and is nonclassifiable as a carcinogen.

- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity

127087-87-0 4-Nonylphenol, branched, ethoxylated

LC50 11.6 mg/l (fish)

- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.
- · Other adverse effects No relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

Page: 7/8

# **Safety Data Sheet**

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: Lag-It

(Cont'd, of page 6)

UN-Number DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.
UN proper shipping name DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.
Transport hazard class(es)	
DOT, ADR/RID/ADN, IMDG, IATA Class	Not regulated.
Packing group DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.
Environmental hazards Marine pollutant:	No
Special precautions for user	Not applicable.

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- Section 302 (extremely hazardous substances):

None of the ingredients are listed.

- · Section 313 (Specific toxic chemical listings):
- 127087-87-0 4-Nonylphenol, branched, ethoxylated
- · TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

- · Proposition 65 (California)
- Chemicals known to cause cancer:

Reference to talc not applicable to product, as product contains no asbestiform fibers.

Reference to titanium dioxide is based on unbound respirable particles and is not applicable to the product as supplied.

14807-96-6	Talc	٦
13463-67-7	Titanium dioxide	

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

(Cont'd, on page 8)

Page: 8/8

# **Safety Data Sheet**

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 11, 2020

Trade name: Lag-It

(Cont'd. of page 7)

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

Reference to titanium dioxide is based on unbound respirable particles and is not applicable to the product as supplied.

13463-67-7 Titanium dioxide

2B

· Canadian Domestic Substances List (DSL):

All ingredients are listed or exempt.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

Acute Tox. 4: Acute toxicity - Category 4

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtel.com